

<p><b>NFPA</b></p> <p>Health: 0, Fire: 1, Reactivity: 0</p>	<p><b>MATERIAL SAFETY DATA SHEET</b></p>	<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <th colspan="2">HMIS</th> </tr> <tr> <td>Health</td> <td style="text-align: center;">0</td> </tr> <tr> <td>Fire</td> <td style="text-align: center;">1</td> </tr> <tr> <td>Reactivity</td> <td style="text-align: center;">0</td> </tr> </table>	HMIS		Health	0	Fire	1	Reactivity	0
HMIS										
Health	0									
Fire	1									
Reactivity	0									

**SECTION I**

PRODUCT NAME OR NUMBER <b>STICK-KUT™ - Lubricating Stick Wax</b>	
MANUFACTURER'S NAME <b>Relton Corporation</b>	EMERGENCY TELEPHONE NO. Chemtrec - (800) 424-9300
ADDRESS (Number, Street, City, State, and Zip Code) 317 Rolyn Place, Arcadia, CA 91007-2838	Non-Emergency Ph. No. (800) 423-1505
HAZARDOUS MATERIALS DESCRIPTION AND PROPER SHIPPING NAME (49 CFR 172.101) NA Solid Lubricant	HAZARD CLASS (49 CFR 172.101) Not Regulated by Dot
CHEMICAL FAMILY Lubricant, Solid Wax, non-hazardous	Formula <b>Mixture</b>

**SECTION II - INGREDIENTS**

SECTION II - INGREDIENTS	TLV	PEL	STEL	C.A.S. NO.	%
Does not contain ingredients identified as Hazardous by 29 CFR, Part 1910.1200					
or Canada - WHMIS Regs.					

**SECTION III - PHYSICAL DATA**

BOILING POINT (°F) (C°) : >425 218	SPECIFIC GRAVITY (H <sub>2</sub> O=1) @ 60° C : .89	VOC : 0.0 lbs/gal
VAPOR PRESSURE (mm Hg) : ND	PERCENT VOLATILE BY VOLUME (%) : 0.00	MELTING POINT (°F) (C°): 104 40
VAPOR DENSITY (AIR=1) : ND	EVAPORATION RATE (BUTYL ACETATE=1): NA	
SOLUBILITY IN: Water: Insoluble Hydrocarbon Solvents: Soluble		
pH as is: NA	MATERIAL IS GAS      LIQUID      SOLID PASTE      POWDER	

**SECTION IV - FIRE AND EXPLOSION HAZARD DATA**

FLASH POINT (method used): 400°F 177°C (COC)	FLAMMABLE LIMITS:	LEL ND	UEL ND
EXTINGUISHING MEDIA: Water fog, dry chemical, foam or CO <sub>2</sub> (agents approved for Class B Hazards)			
SPECIAL FIRE FIGHTING PROCEDURES: Keep personnel removed and upwind of any fire. Wear full fire-fighting turn-out gear (full Bunker gear), and respiratory protection (SCBA).			
UNUSUAL FIRE AND EXPLOSION HAZARDS: None			

**ROUTES OF ENTRY AND SYMPTOMS OF OVEREXPOSURE:**

No normal routes of entry

**SYMPTOMS OF UNUSUAL EXPOSURE:** Eyes, Skin, Lungs: Irritation; Ingestion: Nausea.

**EMERGENCY AND FIRST AID PROCEDURES:**

**EYES:** Flush with copious water for 15 minutes; do not rub. Get medical attention if irritation persists.

**SKIN:** Wash with soap and water.

**INHALATION:** Remove to fresh air; give oxygen or artificial respiration if needed. Consult a physician if difficulties persist.

**INGESTION:** If large amount is swallowed and victim is conscious, induce vomiting.

NE = not established    NF = not found    NA = not applicable    ND = not determined

**SECTION VI - REACTIVITY DATA**

STABILITY:	UNSTABLE		CONDITIONS TO AVOID: Excessive heat (above 125°F)
	STABLE	X	
INCOMPATIBILITY (materials to avoid): Oxidizing agents			
HAZARDOUS DECOMPOSITION PRODUCT: Combustion can produce oxides of C,P,N			
HAZARDOUS	MAY OCCUR		
POLYMERIZATION:	WILL NOT OCCUR	X	

**SECTION VII - SPILL OR LEAK PROCEDURES**

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: If product is melted, allow to solidify; then scrape up.
WASTE DISPOSAL METHOD : Transport in DOT-approved container to EPA-approved treatment, storage, and disposal facility. Follow local, State & Federal disposal regulations.

**SECTION VIII - SPECIAL PROTECTION INFORMATION**

RESPIRATORY PROTECTION (specify type): Normally not needed. For oil-type mist, use NIOSH listed respirator.		
VENTILATION:	LOCAL EXHAUST: If in confined area	SPECIAL: Not required normally
Local-mechanical	MECHANICAL: NA	OTHER: NA
PROTECTIVE GLOVES: Rubber or other impervious gloves if sensitive to the product	EYE PROTECTION: Approved safety glasses, side shields preferred	
OTHER PROTECTIVE EQUIPMENT: Normal work clothing coupled with good hygiene		

**SECTION IX - SPECIAL PRECAUTIONS**

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: Store in a cool, dry place. Don't store near oxidizers.
OTHER PRECAUTIONS: Don't apply to moving tool.

**ADDITIONAL INFORMATION**

<b>DOT:</b> No hazardous substance No hazard class It# 155250 Class 65	<b>UN or NA#:</b> Not applicable <b>Freight Classification:</b> Not Regulated by DOT <b>Shipping Name:</b> Solid Lubricant
<b>SARA:</b> Not considered to be subject to Title III	
<b>TSCA:</b> All components required to be listed on the inventory are listed.	
<b>IARC-NTP-OSHA:</b> Neither the mixture nor any component is listed as a carcinogen or suspected carcinogen.	
<b>Ozone-Depleting Substance:</b> No 1,1,1-Trichloroethane (methyl chloroform) or other ozone-depleting substance No 5/15/93 labeling required.	
<b>California Prop. 65 Material:</b> None	
<b>Canada - WHMIS Regulations:</b> No hazardous substance.	
<b>Canada - Domestic Substances List (DSL):</b> All ingredients in this product are listed on the DSL.	
<b>Note:</b> Although no exposure limits are established, observe ACGIH-OSHA TWA for oil mists: 5Mg/meter <sup>3</sup> . Use with adequate local ventilation and exhaust devices.	

Prepared: 05/01/99 Updated: 03/10/03  
07/22/05  
06/01/10



by Dr. Robert E. Pratt,  
Chemical Consultant



317 ROLYN PLACE, ARCADIA, CALIFORNIA 91007-2838  
Phone: (800) 423-1505 Emerg: Chemtrec - (800) 424-9300