

# STRAIGHT-SHANK MASONRY DRILL BITS

DIAMETER		OVERALL LENGTH	DRILLING DEPTH	PART NO.	LIST PRICE	Wt. (lbs)
POINT	SHANK					
1/8"	1/8"	3"	1 7/8"	RT-2-3*	\$4.00	0.1
5/32"	3/16"	4"	2 3/8"	RT-1-4	8.00	0.1
11/64"	11/64"	3"	1 7/8"	RT-1-3*	8.00	0.1
3/16"	3/16"	3"	1 7/8"	RT-3-3*	5.00	0.1
3/16"	3/16"	4"	2 3/8"	RT-3-4*	6.00	0.1
3/16"	3/16"	6"	4 1/2"	RT-3-6*	8.00	0.1
3/16"	3/16"	8"	6"	RT-3-8*	10.00	0.1
7/32"	1/4"	6"	4"	RT-2-6	8.00	0.1
7/32"	1/4"	8 1/2"	6 1/2"	RT-2-8*	10.00	0.1
1/4"	1/4"	4"	2 1/4"	RT-4-4*	7.00	0.1
1/4"	1/4"	6"	3 3/4"	RT-4-6*	8.00	0.1
1/4"	1/4"	8"	6"	RT-4-8*	13.00	0.1
1/4"	1/4"	12"	10"	RT-4-12	16.00	0.2
1/4"	1/4"	18"	16"	RT-4-18	27.00	0.3
1/4"	1/4"	24"	22"	RT-4-24	33.00	0.4
5/16"	1/4"	4"	2 1/2"	RT-5-4*	9.00	0.1
5/16"	1/4"	6"	4"	RT-5-6*	9.50	0.1
5/16"	1/4"	12"	10"	RT-5-12	19.00	0.3
5/16"	1/4"	18"	16"	RT-5-18	28.00	0.4
3/8"	3/8"	4"	2 1/2"	RT-6-4*	10.00	0.2
3/8"	1/4"	4"	2 1/2"	RT-6-4A	10.00	0.1
3/8"	3/8"	6"	4"	RT-6-6*	11.00	0.2
3/8"	1/4"	6"	4"	RT-6-6A*	11.00	0.2
3/8"	3/8"	12"	10"	RT-6-12	21.00	0.4
3/8"	3/8"	18"	16"	RT-6-18	28.00	0.5
3/8"	3/8"	24"	22"	RT-6-24	38.00	0.7
7/16"	3/8"	4"	2 1/2"	RT-7-4*	10.50	0.2
7/16"	3/8"	6"	4"	RT-7-6*	11.50	0.3
7/16"	3/8"	18"	16"	RT-7-18	36.00	0.6
1/2"	3/8"	4"	2 1/2"	RT-8-4*	11.00	0.2
1/2"	3/8"	6"	4"	RT-8-6*	12.00	0.3
1/2"	1/4"	6"	4"	RT-8-6A*	12.00	0.3
1/2"	3/8"	14"	12"	RT-8-14	26.00	0.6
1/2"	3/8"	18"	16"	RT-8-18	36.00	0.7
1/2"	3/8"	24"	22"	RT-8-24	42.00	0.9
9/16"	3/8"	6"	4"	RT-9-6*	15.00	0.3
5/8"	1/2"	6"	4"	RT-10-6*	17.00	0.4
5/8"	1/2"	14"	12"	RT-10-14	29.00	0.8
5/8"	1/2"	18"	16"	RT-10-18	41.00	1.1
5/8"	1/2"	24"	22"	RT-10-24	46.00	1.3
11/16"	1/2"	6"	4"	RT-11-6*	20.00	0.4
3/4"	1/2"	6"	4"	RT-12-6*	22.00	0.5
3/4"	1/2"	14"	12"	RT-12-14	37.00	1.0
3/4"	1/2"	18"	16"	RT-12-18	44.00	1.5
3/4"	1/2"	24"	22"	RT-12-24	50.00	1.8
7/8"	1/2"	6"	4"	RT-14-6	29.00	0.6
7/8"	1/2"	14"	12"	RT-14-14	41.00	1.3
1"	1/2"	6"	4"	RT-16-6	35.00	0.8
1"	1/2"	18"	16"	RT-16-18	64.00	2.4
1"	1/2"	24"	22"	RT-16-24	73.00	3.1



## ROTARY/PERCUSSION

### RAM TIP™

PROFESSIONAL MASONRY BITS

Relton's **premium** straight-shank masonry bit is designed for use in lightweight, rotating-vibrating hammers, but it can be used equally well in standard drill motors as a rotary bit.

A special hard, tough carbide cutter is precisely located for maximum support and strength.

Shank diameters 3/8" and larger have 3 flats on the shank to reduce the possibility of slipping in the chuck.

*All RT bits are available in GRT® style, See page 12 for additional information.*

## RAM TIP™ STRAIGHT SHANK 5-PIECE BIT KIT



Refillable Case  
Contains: 3/16" x 6"  
1/4" x 6"  
5/16" x 6"  
3/8" x 6"  
1/2" x 6"

### RAM-TIP™

PART NO.	LIST PRICE	WT. (lbs)
RT-K5	\$ 49.00	0.7

**\* 25 pc. quantities available in bulk packaging**  
To order bulk, use prefix "B" before part number. Example: **BRT-8-6**

